



# OSHA ROOF STAIRS

## PRODUCT FEATURES

- 1. ALWAYS COMPLIANT** – completely OSHA or ADA compliant with equal step riser heights and guardrails.
- 2. SLIP-RESISTANT DECKING** – we offer standard extruded decking, aggressive grip strut decking, or bar grating to accommodate different environments and needs.
- 3. LONG PRODUCT LIFECYCLE** – our products are rust-free which means they are a low-maintenance material and have a long product lifecycle.
- 4. CUSTOMIZED LAYOUTS** – our team of engineers will design custom layouts for your toughest projects. Professional Engineer stamps available.
- 5. PROFESSIONAL INSTALLATION** – Upside’s professional installation crew will come to your site to install your rooftop access stairs to make sure it’s done right the first time.

## QUICK SPECS

<b>MATERIAL</b>	Mill finish aluminum extrusions and sheet (optional: grip strut tread)
<b>HEIGHT</b>	Custom heights
<b>WIDTH</b>	No less than 22” between handrails
<b>TREAD DEPTH</b>	11” + 1” nosing
<b>RISER HEIGHT</b>	6” , 6.5” , or 7”
<b>HANDRAIL</b>	36” high
<b>PLATFORM SIZE</b>	Custom to your application
<b>PLATFORM GUARDRAILS</b>	42” high
<b>WEIGHT CAPACITY</b>	100 LBS./Ft <sup>2</sup> Live Load, 300 LBS./Ft <sup>2</sup> Point Load

\*The specifications above are standard dimensions, but our team has the capability to design a solution that will fit your application.