



ADA RAMPS

PRODUCT FEATURES

1. **NEVER RUSTS, WARPS, ROTS** – aluminum will never rust which means our products will have a clean appearance for longer.
2. **LOW MAINTENANCE** – our aluminum does not require regular maintenance for weather protection while other materials do.
3. **FAST INSTALLATION** – typically takes between 5 and 6 hours to install a ramp.
4. **ADJUSTABLE** – platform and ramp legs are adjustable to accommodate uneven ground.
5. **CUSTOM LAYOUTS** – our ramps can be configured (and reconfigured) for your exact layout needs and can be paired with any of our canopy and stair products.

QUICK SPECS

MATERIAL	Mill finish aluminum extrusions and sheet
LENGTH	Any length – made of 8' & 10' ramp sections that piece together
WIDTH	48" between handrails, 60" out-to-out
PLATFORM SIZES	64" x 64", 64" x 96", 72" x 72" (other sizes available)
GUARDRAIL	42" high
HANDRAIL	36" high
CHILD HANDRAIL (OPTIONAL)	18" high
SLOPE	1:12
BALUSTERS	Less than 4" apart
WEIGHT CAPACITY	Live load: 100 lbs. per sqft. Point load: 300 lbs. over a sqft area.
POWDER COATING (OPTIONAL)	Ask a solutions advisor for all color options

*The specifications above are standard dimensions, but our team has the capability to design a solution that will fit your application.