



DUAL STEPS

PRODUCT FEATURES

- 1. OSHA COMPLIANT** – equal step tread heights and the two-line rail system keeps employees safe while accessing mobile offices and trailers.
- 2. FAST INSTALLATION** – typically takes less than half an hour to install a Dual Step and platform.
- 3. ADJUSTABLE** – can be adjusted to meet two different heights. For example, the 28”/35” Dual Step can be set at either 28” OR 35” tall.
- 4. SLIP-RESISTANT DECKING OPTIONS** – choose between knurled, extruded decking material or grip strut decking.
- 5. DURABLE** – aluminum will never rust, warp, or rot which means the structural integrity will remain intact for longer.



Set at 28” threshold height



Set at 35” threshold height

QUICK SPECS

MATERIAL	Mill finish aluminum extrusions and sheet
HEIGHT	We have three sizes of Dual Steps: 28”/35”, 35”/42”, 42”/49”
WIDTH	39 1/2” between handrails (or one handrail and the building), 43” out-to-out
TREAD DEPTH	9 1/2”
RISER HEIGHT	7” rise
HANDRAIL	36” high
PLATFORM SIZES	Extruded decking: 58” x 43”, Grip Strut: 59 1/4” x 43”
PLATFORM GUARDRAILS	42” high
WEIGHT CAPACITY	100 lbs/sqft Live Load, 300 lbs over a sqft area

*The specifications above are standard dimensions, but our team has the capability to design a solution that will fit your application.