




LOADING DOCK STEPS

PRODUCT FEATURES

- 1. NEVER RUSTS, WARPS, ROTS** – aluminum will never rust which means it will have a clean appearance for longer.
- 2. LOW MAINTENANCE** – our aluminum does not require regular maintenance for weather protection while other materials do.
- 3. FAST INSTALLATION** – typically takes between 1 and 3 hours to install a single-story step system.
- 4. COMPLETELY CUSTOMIZABLE** – choose your decking, handrail style, and riser type to complete



Fiber Grate Grip Strut Extruded Bar Grating



CLOSED BACK



OPEN BACK



BALUSTER
HANDRAILS



TWO-LINE
RAILS

QUICK SPECS

HEIGHT	Reach variety of heights by using either 6", 6.5", or 7" step rises
WIDTH (W/ BALUSTER HANDRAILS)	51-3/4" between handrails, 64" out-to-out
WIDTH (W/ TWO-LINE RAILS)	59-3/4" between guardrails, 64" out-to-out
TREAD DEPTH	12" nosing
PLATFORM SIZES	67" x 67"
PLATFORM GUARDRAIL	42" high
STEP GUARDRAIL	42" high (only applicable to baluster handrails)
HANDRAIL	36" high
BALUSTERS	Less than 4" apart (only applicable to baluster handrails)
WEIGHT CAPACITY	100 lbs/sqft Live Load, 300 lbs over a sqft area
POWDER COATING (OPTIONAL)	Ask a solutions advisor for all color options

*The specifications above are standard dimensions, but our team has the capability to design a solution that will fit your application.