



OMNI STEPS

PRODUCT FEATURES

- 1. OSHA COMPLIANT** – the pivoting step riser maintains equal step tread heights to make sure employees are safe.
- 2. FAST INSTALLATION** – typically takes less than half an hour to install an Omni Step and platform.
- 3. ADJUSTABLE** – completely adjustable between the specified range. For example, the 21” – 26” Omni system can reach any height between 21” and 26” tall.
- 4. REUSABLE** – Omni Steps can be relocated and adjusted to meet the new application’s height as you move the mobile office or trailer.
- 5. SLIP-RESISTANT DECKING** – knurled, extruded decking material for added traction.
- 6. DURABLE** – aluminum will never rust, warp, or rot which means the structural integrity will remain intact for longer.

QUICK SPECS

MATERIAL	Mill finish aluminum extrusions and sheet
HEIGHT	We have three sizes of Omni Steps: 21” – 26”, 28” – 35”, 35” – 44”
WIDTH	37 5/8” between handrails (or one handrail and the building), 41” out-to-out
TREAD DEPTH	9 1/2”
RISER HEIGHT	7” – 8 13/16” (gets smaller or bigger as threshold height lowers or raises)
HANDRAIL	36” high
PLATFORM SIZES	56 3/4” x 41”
PLATFORM GUARDRAILS	42” high
WEIGHT CAPACITY	100 lbs/sqft Live Load, 300 lbs over a sqft area

*The specifications above are standard dimensions, but our team has the capability to design a solution that will fit your application.