



NOTES:

1. ALL GUARDRAILS MOUNT TO THE SIDE FACE OF THE CONCRETE WITH (2) 3/8" X 3 3/4" WEDGE ANCHORS PER POST (MINIMUM).
2. GUARDRAILS AND CANOPY ARE CONSTRUCTED OF WELDED ALUMINUM.
3. THE DOOR SHOWN IS NOT TO BE USED AS AN ADA EGRESS.
4. ALL GUTTERS ARE SUPPORTED BY 4" X 4" POSTS AT LOCATIONS SHOWN.
5. WATER DRAINS THROUGH SUPPORT POSTS AND EXITS NEAR THE BOTTOM ABOVE GRADE.
6. CANOPY IS POWDER COATED IN STANDARD WHITE FINISH.

DWG #	12673
DATE	5/26/17
REVISION	A
SCALE	1:40
DRAWN	SRF
CHECKED	KRS
TITLE	

UPSIDE UPSIDE INNOVATIONS LLC CINCINNATI, OHIO WWW.UPSIDENOVATIONS.COM PHONE: (513) 889-2492 FAX: (513) 672-2124	
DATE	5/26/17
BY	SF
REV	A
ADDED POSTS AT WALL TO MAKE CANOPY	
FREE-STANDING	

ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED	XXX ± 0.06" FRACTIONAL ± 1/16"	XXXX ± 0.030" ANGLES ± 1°
DATE	BY	REV
5/26/17	SF	A
ADDED POSTS AT WALL TO MAKE CANOPY		
FREE-STANDING		

The concepts and designs shown here-in are the exclusive proprietary property of UPSIDE INNOVATIONS LLC and may not be copied or used in any manner without written permission from UPSIDE INNOVATIONS.