



OSHA HILLSIDE STEPS

PRODUCT FEATURES

1. **NEVER RUSTS, WARPS, ROTS** – aluminum will never rust which means it will have a cleaner appearance for longer.
2. **LOW MAINTENANCE** – our aluminum does not require regular maintenance for weather protection while other materials do.
3. **PROFESSIONAL INSTALLATION** – to make sure your project goes smoothly, we offer installation by our professional installation crew.
4. **ALWAYS COMPLIANT** – we design our product to meet all of the OSHA code requirements.
5. **CUSTOMIZED LAYOUTS** - we manufacture each set of OSHA stair towers to meet the specific application, and we provide you with site-specific layout drawings.

QUICK SPECS

MATERIAL	Mill finish aluminum extrusions and sheet (optional: grip strut tread)
HEIGHT	Custom heights
WIDTH	No less than 22" between handrails
TREAD DEPTH	12"
RISER HEIGHT	Any rise to meet the overall height (30° - 50° from horizontal)
HANDRAIL	36" high
PLATFORM SIZE	Custom to your application
PLATFORM GUARDRAILS	42" high
WEIGHT CAPACITY	100 LBS/sqft Live Load, 300 LBS over a sqft area
FOOTINGS	16" diameter, check with local building inspection dept. for depth requirement

*The specifications above are standard dimensions, but our team has the capability to design a solution that will fit your application.