



- NOTES:
1. STAIR TREADS ARE 48" WIDE, CLEARANCE BETWEEN HANDRAILS IS 49".
 2. ALL STAIR TREADS ARE 10" DEEP AND 7-7/8" HIGH.
 3. ALL HANDRAILS ARE 36" HIGH AND ARE 1-5/8" OD ROUND TUBE.
 4. ALL GUARDRAILS ARE 42" HIGH AND ARE 1-3/4" SQUARE TUBE.
 5. ALL PLATFORM GUARDRAILS HAVE A 4" HIGH TOE KICK PLATE TO PREVENT FEET FROM SLIPPING OFF THE EDGE OF THE PLATFORMS.
 6. STAIR TREADS AND PLATFORM WALKING SURFACES ARE CONSTRUCTED OF OPEN GRIP SAFETY GRATING.
 7. ALL ALUMINUM CONSTRUCTION WITH STAINLESS STEEL FASTENERS.
 8. STAIR TOWER DEAD LOAD IS 8900 LBS.

DATE	REVISION	SCALE	DRAWN	CHECKED	TITLE	DATE	BY	REV	REVISION DESCRIPTION
		1:50	SRF	KRS					

ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED XXX + 0.06" FRACTIONAL ± 1/16" XXXX + 0.030" ANGLES ± 1'

UPSIDE INNOVATIONS LLC CINCINNATI, OHIO
WWW.UPSIDEINNOVATIONS.COM
PHONE: (513) 888-2402 FAX: (513) 872-9124

The concepts and designs shown here-in are the exclusive proprietary property of UPSIDE INNOVATIONS LLC and may not be copied or used in any manner without written permission from UPSIDE INNOVATIONS.